



Main

Range of product	Actassi
Product or component type	Patch cord
Product compatibility	Coloured clips yellow Coloured clips blue Coloured clips red Coloured clips green
Communication network category	6A
Colour	Grey patchcord

Complementary

Provided equipment	Coloured clips green Coloured clips red Coloured clips grey
Cable shielding type	S/FTP
Communication network type	10GBASE-T
Transmission frequency	550 MHz
Input impedance	100 Ohm
Connector type	RJ45
Material	Solid bare copper conductor PE (polyethylene) wire insulation
Standards	ISO/IEC 11801:2011 Ed.2.2 EN 50173 Ed.3 EIA/TIA-568-C.2 IEC 61935-2
Product certifications	Delta
Quantity per set	1
Cable length	3 m

Environment

Environmental characteristic	LSZH (low smoke zero halogen) jacket
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-20...60 °C
Ambient air temperature for installation	0...50 °C
Temperature resistance	60 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1144 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------