


[Home](#) » [IP Surveillance](#) » [IP Camera](#) » [H.265 IP Camera](#) » [ICA-4460V](#)



## H.265 4MP PoE Dome IR IP Camera with Vari-focal Lens

» [ICA-4460V](#)



[Overview](#)

[Applications](#)

[Key Features](#)

[Specifications](#)

[Downloads](#)

[Related Products](#)

### Camera

- 1/3" progressive scan CMOS sensor
- 2.8~12 mm vari-focal, fixed-iris lens
- 0.01 lux minimum illumination at F1.2
- Maximum resolution 2592 x 1520
- 36 built-in powerful IR illuminators, effective up to 20~40 meters
- Removable IR-cut filter for Day & Night function

### Video and Audio

- Simultaneous H.264 and H.265 video compression
- Simultaneous multi-stream support
- Max. resolution of 4 mega-pixel (2592 x 1520 pixel)
- DNR to improve picture quality at low lux
- WDR enhancement function strengthens visibility under extremely bright or dark environments
- Two-way audio support with enhanced audio quality

### Network and Configuration

- Compliant with IEEE 802.3af/at PoE interface for flexible deployment
- RTSP (Real Time Streaming Protocol) protocols selectable
- FTP uploading supports more alternatives in surveillance network
- PLANET DDNS and Easy DDNS support

### Easy Installation and Management

- ONVIF compliant for interoperability
- IP66-rated housing and waterproof RJ45 connector for rigorous environment
- Intelligent motion detection alarm
- Easy configuration and management via Windows-based utility or web interface

### Ordering Information

ICA-4460V	H.265 4MP PoE Dome IR IP Camera with Vari-focal Lens
-----------	--

[Corporate Responsibility](#)  
[Awards](#)  
[Contact Us](#)

[PLANET eTV](#)  
[News](#)  
[Events](#)

[Corporate APP](#)